HALTMASTER® TRAFFIC MANAGEMENT

PRODUCT DATA SHEET

Published August 2023



Haltmaster Corner Protection

HMCP330 Haltmaster Corner Protection – Impact Absorbing Polyurethane foam core with a hard plastic outer, recommended for installation on Corners of Underground Carparks for Transport Sectors.



FREEDOM

SPECIFICATIONS

Masterspec Code	Interior: 8262HM
Warranties	Installation warranty: 1 year
	Product warranty: 10 years
Temperature Rating	Range from –40 degrees C to 100 degrees C
Code Compliance	NZ Transport Agency Traffic Con
	trol Devices Manual (TCD Manu
	al) - Performance requirements
	for barrier systems, including
	corner protection systems, and
	provides guidance on the
	selection and installation of such
	systems.
	AS/NZS 2890:1:2004 - Clause
	2.5.8 - "Protection of buildings and
	other structures."

Material	Polyurethane Foam Core
Finish	Sealed Finish
Dimensions	Thickness: 12 mm
	Width: 60mm
	Inner Width: 48 mm
	Length: 1000 mm
Features	A hard impacts preventing
	injury and damage, provides
	high visibility to danger zones,
	is moisture resistant making
	them suitable for interior and
	exterior applications, are
	flexible so can be fitted to
	curved surfaces. Used on steel
	columns, pallet racking, walls,
	corners and anywhere.
Installation Methods	Double sided tape and adhesive fixed

8 Cooper Street, Havelock North 4130 PO Box 8740, Havelock North 4130

Unit 2, 24 Inlet Road, Takanini Auckland 2112

09 320 1338 or Toll Free 0800 687 004

ARCHITECTURAL PRODUCTS



TRAFFIC MANAGEMENT





HALTMASTER® TRAFFIC MANAGEMENT



PRODUCT TECHNICAL DRAWING

PREVIOUS PROJECTS









