



GUIDEMASTER®

TACTILE INDICATORS



PRODUCT DATA SHEET

Published August 2023

GMSSC30

Guidemaster Warning Tactile Indicator—316 Marine Grade Stainless Steel with Yellow Carborundum

GMSSC30 Guidemaster Tactile Ground Surface Indicator – A Heavy Duty 316 marine grade stainless steel warning tactile indicator with yellow inner and outer carborundum, recommended for indoors and outdoors, commercial carparks, footpaths, shopping centres, hospitals, schools – any public spaces requiring accessibility treatment.



SPECIFICATIONS

Masterspec Code	Interior: 6615FG / Exterior: 8281FG
Warranties	Installation warranty: 1 year Product warranty: 10 years
Luminance Test	Provides colour contrast. Discrete Tactiles must be 45% to that of the surround substrate surface area.
Code Compliance	NZTA RTS14 —Land Transport New Zealand – Guidelines for facilities for the blind and vision impaired. AS/NZS 1428.4.2009 —Design for access and mobility, Part 4 NZS4121:2001 —Design for access and mobility—building and associated facilities All slip resistance tests are done in accordance with AS/NZS4586:2004 Land Transport's Pedestrian Planning and Design Guide The Royal N.Z. Foundation for the Blind Design Guide Recommendations/ Specifications


Base Material	316 Marine Grade Stainless Steel Base with Highly abrasive Yellow Inner and Side Carborundum
Dimensions	Outer: 35mm Top: 25mm
Features & Application	Provides warning to the blind and visually impaired
Installation Methods	Drill and Adhesive Fix or Drill and Friction Fit in accordance to New Zealand Standards
Sustainability	Declare Label Certified LBC Compliant—Red List Approved
Slip Resistance Rating	P5 WET and DRY - SRV Value of 72 and 93





GUIDEMASTER®

TACTILE INDICATORS



PRODUCT TECHNICAL DRAWING

