



Traffic Management - HMWS1830 Technical Data Sheet

| | | |
|---------------------------|---|----------|
| Product Name | HMWS1830 Heavy Duty Wheel Stops 1830mm | |
| Description | Recycled Rubber Wheel Stop, recommended for installation on Carparks and Civil and Transport Sector | |
| Freedom Works Code | HMWS1830 | |
| Masterspec Code | Interior | 8262HM |
| Warranty | Installation Warranty | 1 year |
| | Product Warranty | 10 years |

freedomworks.co.nz
sales@freedomworks.co.nz

09 320 1338
0800 687 004

Scan to visit the webpage



| | | |
|------------------------|---|--|
| Code Compliance | NZ Transport Agency Traffic Control Devices Manual (TCD Manual) | Section 1.6.4 of the rule provides guidance on the design and placement of wheel stops in parking areas. |
| | AS/NZS 2890:1:2004 | Off street car parking Specifications |
| | NZS 2295:2006 | Parking Caravan, Motor Caravan and Bus Parks |

| | | |
|----------------------------|---|-------------------------------|
| Base Material | Recycled Rubber | |
| Features | Single piece rubber wheel stop manufactured from premium durable black rubber with a gritty yellow reflective strip that provides maximum visibility during the day and night. Used to prevent vehicles from travelling into other parking spaces or surrounding buildings. Will not chip or cor-rose. Flexible and conform to most road surfaces | |
| Dimensions | Length | 1830mm |
| | Height | 100mm |
| | Width | 150mm (at base) |
| | Weight | 18kg |
| Installation Method | Mechanical Fixing | |
| | Concrete Surface | 4 No 180 mm x 12 mm Tru bolts |
| | Asphalt Surface | 4 No 300 mm x 12 mm Tru bolts |
| | Requires 4 fixing per Wheel Stop | |



Traffic Management - HMWS1830 Technical Drawings & Imagery

| | |
|-------------------------|--|
| <p>Side View</p> | |
| <p>Top View</p> | |
| <p>End View</p> | |

freedomworks.co.nz
sales@freedomworks.co.nz

09 320 1338
0800 687 004

Scan to visit the webpage



| | |
|-----------------------------|--|
| <p>Product Image</p> | |
|-----------------------------|--|