



## Stair Nosings & Inserts – SMN210 Technical Data Sheet

<b>Product Name</b>	SMN210 Stair Nosing	
<b>Description</b>	Anodised Aluminium base with a Solid Carborundum Insert, recommended for surface mounting on Accessible Stairs, Fire Egress, Back of House, Common Stairs and Service Stairs	
<b>Freedom Works Code</b>	SMN210	
<b>Masterspec Code</b>	6614FS	
<b>Warranty</b>	Installation Warranty	1 year
	Product Warranty	10 years

freedomworks.co.nz  
sales@freedomworks.co.nz

09 320 1338  
0800 687 004

Scan to visit the webpage




<b>Code Compliance</b>	NZBC D1/AS1	Access routes
	NZS 4121	Design for access and mobility

<b>Base Material</b>	Alloy: 6060, Temper: T5	
<b>Finish</b>	Silver, Black, Bronze or Gold Anodized – 30 µm	
<b>Dimensions</b>	Tread Width	85mm
	Front Depth	35mm
	Tread Thickness	5mm
<b>Installation Method</b>	Adhesive Only or Mechanical and Adhesive Fixing	
	Masonry screw 6mm x 30mm	
<b>Insert Type</b>	Solid epoxy based Carborundum – Heavy Duty, External Grade	
<b>Insert Width</b>	54mm	
<b>Insert Colours</b>	Black, Safety Yellow, Luminescent, Grey – other colours available on request	
<b>Application</b>	Predrilled and countersunk for secret screw fixing – One installed, insert covers all fixing	
<b>Sustainability</b>	Declare Label Certified	
	LBC Compliant	Red List Approved
<b>Slip Ratings</b>	Slip Resistance	AS/NZS 4586: 2004 Slip Resistance
	Rating	Average COF of 73



Stair Nosings & Inserts - SMN210  
Technical Drawings & Imagery



[freedomworks.co.nz](http://freedomworks.co.nz)  
[sales@freedomworks.co.nz](mailto:sales@freedomworks.co.nz)

09 320 1338  
0800 687 004

Scan to visit the webpage

