



## Stair Nosings & Inserts - SMN212

### Technical Data Sheet

|                           |  |          |
|---------------------------|--|----------|
| <b>Product Name</b>       | SMN212 Stair Nosing  |          |
| <b>Description</b>        | Anodised Aluminium base with a Solid Carborundum Insert, recommended for surface mounting on Accessible Stairs, Fire Egress, Back of House, Common Stairs and Service Stairs |          |
| <b>Freedom Works Code</b> | SMN212   |          |
| <b>Masterspec Code</b>    | 6614FS   |          |
| <b>Warranty</b>           | Installation Warranty  | 1 year   |
|                           | Product Warranty   | 10 years |

freedomworks.co.nz  
sales@freedomworks.co.nz

09 320 1338  
0800 687 004

Scan to visit the webpage




|                        |             |                                |
|------------------------|-------------|--------------------------------|
| <b>Code Compliance</b> | NZBC D1/AS1 | Access routes                  |
|                        | NZS 4121    | Design for access and mobility |

|                            |  |                                   |
|----------------------------|--|-----------------------------------|
| <b>Base Material</b>       | Alloy: 6060, Temper: T5  |                                   |
| <b>Finish</b>              | Silver, Black, Bronze or Gold Anodized – 30 µm   |                                   |
| <b>Dimensions</b>          | Tread Width  | 68mm                              |
|                            | Front Depth  | 10mm                              |
|                            | Tread Thickness  | 5mm                               |
| <b>Installation Method</b> | Adhesive Only or Mechanical and Adhesive Fixing  |                                   |
|                            | Masonry screw 6mm x 30mm   |                                   |
| <b>Insert Type</b>         | Solid epoxy based Carborundum – Heavy Duty, External Grade                                   |                                   |
| <b>Insert Width</b>        | 55mm   |                                   |
| <b>Insert Colours</b>      | Black, Safety Yellow, Luminescent, Grey – other colours available on request                 |                                   |
| <b>Application</b>         | Predrilled and countersunk for secret screw fixing – One installed, insert covers all fixing |                                   |
| <b>Sustainability</b>      | Declare Label Certified  |                                   |
|                            | LBC Compliant  | Red List Approved                 |
| <b>Slip Ratings</b>        | Slip Resistance  | AS/NZS 4586: 2004 Slip Resistance |
|                            | Rating   | Average COF of 73                 |



Stair Nosings & Inserts - SMN212  
Technical Drawings & Imagery



freedomworks.co.nz  
sales@freedomworks.co.nz

09 320 1338  
0800 687 004

Scan to visit the webpage

