

## Walkway Inserts - SMW10 Technical Data Sheet

<b>Product Name</b>	SMW10 Walkway Insert - Silver	
<b>Description</b>	Anodised strips with solid Carborundum infill for rebating into ready made timbers	
<b>Freedom Works Code</b>	SMW10	
<b>Masterspec Code</b>	Interior	4391FS
<b>Warranty</b>	Installation Warranty	1 year
	Product Warranty	10 years

freedomworks.co.nz  
sales@freedomworks.co.nz

09 320 1338  
0800 687 004


Scan to visit the webpage



<b>Code Compliance</b>	Clause 2.0 of NZBC D1 Acceptable Solutions and Verification Methods	Access Routes
	AS 4586: 2013	Slip Resistance classification for new pedestrian surface materials
	NZS 4121:2001	Design for Access and Mobility

<b>Slip Resistance</b>	Rating 90mm Timber	AS/NZS 4586: 2004 Slip Resistance
		Transverse Direction SRV of 20
		Longitudinal Direction SRV of 50
	Rating 140mm Timber	Transverse Direction SRV of 62
		Longitudinal Direction SRV of 57

<b>Channel Profile</b>	Aluminium Alloy: 6060, Temper: T5	
<b>Finish</b>	Silver Anodized—30 µm	
<b>Dimensions</b>	90mm Timber Width	2 Inserts Spacing
		Timber edge to centre of insert: 27mm
		Centre to centre of insert: 36mm
	140mm Timber Width	3 Inserts Spacing
		Timber edge to centre of insert: 37mm
		Centre to centre of insert: 33mm
	Width	14mm
Depth	6.20mm	
<b>Rebate Size</b>	Recommended rebate size is 14mm wide and 7mm deep	
<b>Infill Type</b>	Solid epoxy based Carborundum – Heavy Duty, External Grade	
<b>Infill Colour</b>	Black	
<b>Features</b>	Rebated for long term durability. Flush for to create non bumpy access for wheeled traffic while providing a high slip resistant finish.	
<b>Sustainability</b>	Declare Label Certified	
	LBC Compliant	Red List Approved
	Reduced waste, lower carbon emissions, enhanced durability and improve safety	



## Walkway Inserts - SMW10 Technical Drawings & Imagery

freedomworks.co.nz  
sales@freedomworks.co.nz

09 320 1338  
0800 687 004

Scan to visit the webpage

